



表1：LMシリーズ寸法表

軸径 (mm)	スタンダード 標準型 両シール付	主要寸法 (mm)								玉列数	質量 (kg)	基本定格荷重			
		d	D		L		ℓ		w			Do	C (N)	Co (N)	
6	LM6-UU	6	0 -0.009	12	0 -0.011	19	0 -0.2	13.5	0 -0.2	1.1	11.5	4	0.007	218	160
8	LM8-UU	8		15		24		17.5		1.1	14.3	4	0.014	258	220
10	LM10-UU	10		19		29		22		1.3	18.0	4	0.026	532	430
12	LM12-UU	12		21	0 -0.013	30		23		1.3	20.0	4	0.032	549	430
13	LM13-UU	13		23		32		23		1.3	22.0	4	0.040	555	440
16	LM16-UU	16		28		37		26.5		1.6	26.6	5	0.07	768	650
20	LM20-UU	20	32		42	30.5	1.6	30.3	5	0.09	1282	1010			
25	LM25-UU	25	0 -0.010	40	0 -0.016	59	0 -0.3	41	0 -0.3	1.85	38.0	6	0.21	2164	1790
30	LM30-UU	30	45		64	44.5		1.85		43.0	6	0.24	3245	2510	
35	LM35-UU	35	52		70	49.5		2.1		49.0	6	0.35	3521	3090	
40	LM40-UU	40	0 -0.012	60	0 -0.019	80		60.5		2.1	57.0	6	0.77	4844	4040
50	LM50-UU	50	80		100	74		2.6		76.5	6	1.43	8272	6430	
60	LM60-UU	60	0 -0.015	90	0 -0.022	110		85		3.15	86.5	6	2.20	9847	7270

*標準品材質：SUJ-2

