



表：RBSMA (C10 class) シリーズ寸法表 (標準, 中リード)

単位：mm

型番	加工区分	呼び		ネジ軸		ナット主要寸法							ボール径	循環数	基本定格荷重		最大ネジ軸長	質量		
		外径 d	リード ℓ	谷径 d ₁	軸端 L ₁	D	Lt	Df	T	W	PCD	X			E	Dw		Ca (kN)	Coa (kN)	L ₀
RBSMA0802	R	8	2	6.6	55	20	28	40	6	24	30	4.5	—	1.588	3.5×1	1.8	3.2	400	0.09	0.40
RBSMA1004	R	10	4	7.8	60	26	34	46	8	28	36	4.5	—	2.381	2.5×1	2.3	4.8	600	0.18	0.60
RBSMA1204	R	12	4	10.0	60	30	35	50	8	30	40	4.5	—	2.381	2.5×1	2.6	5.8	800	0.22	0.87
RBSMA1210	R		10	9.6			44	54	12	32	41	5.5	5	3.175	1.5×1	2.9	5.0		0.26	0.90
RBSMA1505	R	15	5	12.5	60	34	40	54	10	34	44	4.5	5	3.175	2.5×1	5.1	10.5	1200	0.25	1.38
RBSMA1510	R		10				52	57		45	5.5	5.1							10.5	0.35
RBSMA2005	R	20	5	17.5	80	40	40	60	10	40	50	4.5	5	3.175	2.5×1	6.2	14.7	2000	0.37	2.46
RBSMA2010	R		10	16.3			52	57	82	12	52	67							6.6	4.762
RBSMA2505	R	25	5	21.8	110	43	40	67	10	43	55	5.5	5	3.175	2.5×1	6.5	18.7	2500	0.42	3.84
RBSMA2510	R		10	20.3			60	92	96	15	60	78							9	6.35
RBSMA2806	R	28	6	25.6	150	50	65	80	12	50	65	6.6	6	3.175	2.5×2	12.1	42.3	2500	0.81	4.82
RBSMA3210	R	32	10	27.2	150	67	92	103	15	67	85	9	5	6.35	2.5×2	32.8	86.7	3000	2.14	6.30
RBSMA3610	R	36	10	31.1	200	70	93	110	17	70	90	11	7	6.35	2.5×2	35.1	98.2	3000	2.31	7.97
RBSMA3620	R		20				89									35.1	98.2		2.23	7.97
RBSMA4010	R	40	10	35.1	200	76	93	116	17	76	96	11	7	6.35	2.5×2	37.1	105.6	4000	12.5	9.84

* R：転造品

呼び番号 **RBSMA20** **05** × **1000**
 ネジ軸外径 | リード | ネジ軸長さ