



表：TMK, TMK-OHシリーズ寸法表（右，左ネジ）

単位：mm

ナット型番		ナット主要									
油穴なし 右ネジ 左ネジ	油穴付 右ネジ 左ネジ	ピッチ P	D_{hs}	Df	P.C.D.	K	L	R	r	T	F
TMK10	TMK10-OH	2	20	36	26	22	24	1	0.5	5	6
TMK10L	TMK10L-OH										
TMK12	TMK12-OH	2	22	44	31	24	30	1	0.5	5	7
TMK12L	TMK12L-OH										
TMK14	TMK14-OH	3	22	44	31	24	30	1	0.5	5	7
TMK14L	TMK14L-OH										
TMK16	TMK16-OH	3	28	51	38	30	35	1	0.5	6	8
TMK16L	TMK16L-OH										
TMK18	TMK18-OH	4	32	56	42	34	40	1.5	0.5	6	10.5
TMK18L	TMK18L-OH										
TMK20	TMK20-OH	4	32	56	42	34	40	1.5	0.5	6	10.5
TMK20L	TMK20L-OH										
TMK22	TMK22-OH	5	36	61	47	40	50	1.5	0.5	7	14
TMK22L	TMK22L-OH										
TMK25	TMK25-OH	5	36	61	47	40	50	1.5	0.5	7	14
TMK25L	TMK25L-OH										
TMK28	TMK28-OH	5	44	76	58	48	56	2	0.5	8	15
TMK28L	TMK28L-OH										
TMK32	TMK32-OH	6	44	76	58	48	56	2	0.5	8	15
TMK32L	TMK32L-OH										
TMK36	TMK36-OH	6	52	84	66	56	60	2	0.5	8	17
TMK36L	TMK36L-OH										
TMK40	TMK40-OH	6	58	98	76	62	70	2	0.5	10	19
TMK40L	TMK40L-OH										

* 右ネジは軸径の後無記号，左ネジは軸径の後にL記号で表示します。

寸法							ネジ軸型番		ネジ軸主要寸法				
S	H	W	Ro	t	Fa (kN)	質量 (kg)	右ネジ 左ネジ	有効径 d	谷径 d_o	リード角 d_i	α°	質量 (kg/m)	
4.3	1.5	2.5	1.8	0.5	1.2	0.07	TM10 TM10L	10	9	8	4°03'	0.6	
5.4	1.5	2.5	1.8	0.5	1.9	0.10	TM12 TM12L	12	11	10	3°19'	0.8	
5.4	1.5	2.5	1.8	0.5	2.3	0.09	TM14 TM14L	14	12.5	11	4°22'	1.0	
6.6	1.5	2.5	1.8	0.5	3.1	0.18	TM16 TM16L	16	14.5	13	3°46'	1.3	
6.6	2	3	2.5	0.5	4.1	0.23	TM18 TM18L	18	16	14	4°33'	1.6	
6.6	2	3	2.5	0.5	4.6	0.23	TM20 TM20L	20	18	16	4°03'	2.0	
6.6	2.5	3.5	2.5	0.7	5.8	0.38	TM22 TM22L	22	19.5	17	4°40'	2.3	
6.6	2.5	3.5	2.5	0.7	6.6	0.31	TM25 TM25L	25	22.5	20	4°03'	3.1	
9	2.5	3.5	2.5	0.7	8.5	0.57	TM28 TM28L	28	25.5	23	3°34'	4.0	
9	2.5	3.5	2.5	0.7	9.8	0.52	TM32 TM32L	32	29	26	3°46'	5.2	
9	3	4	3.2	0.7	12.0	0.76	TM36 TM36L	36	33	30	3°19'	6.7	
11	3	4	3.2	0.7	16.0	1.09	TM40 TM40L	40	37	34	2°57'	8.4	

呼び番号 ナット型番 ネジ軸型番
 TMK20 - TM20 × 500
 ネジ軸外径 | ネジ軸長さ