



表304 : BSPF, BSPKシリーズ寸法表

単位 : mm

型番	主要寸法											玉条列	基本定格荷重		基本定格トルク		静的許容モーメント M _{A1} (N·m)	質量 ナット (kg)	軸 (kg/m)	最大軸長
	D ₀₆	D _f	K	PCD	L _t	L ₁	T	F	M	H	d ₀₇		C	C ₀	C _T	C _{0T}				
BSPF6	14	30	—	22	28	16.7	5	7.5	M3	1	6	2	0.92	1.75	3.12	5.90	3.82	0.035	0.22	1000
BSPK6			18															0.029		
BSPF8	16	32	—	24	32	17.7	5	7.5	M3	1	8	2	0.98	1.91	4.30	8.36	3.82	0.043	0.39	1000
BSPK8			20															0.036		
BSPF10	21	42	—	32	36	20	6	10.5	M4	1.5	10	2	1.98	3.20	11.26	18.17	9.31	0.088	0.60	1000
BSPK10			26															0.075		
BSPF13	24	44	—	33	40	24	7	11	M4	1.5	13	2	2.98	4.90	21.78	35.78	14.70	0.12	1.03	1500
BSPK13			30															0.10		
BSPF16	31	51	—	40	53	34	7	18	M4	1.5	16	2	3.66	6.54	32.00	57.19	36.36	0.22	1.56	1500
BSPK16			37															0.20		
BSPF20	35	58	—	45	66	46.7	9	22.5	M5	2	20	2	5.68	10.67	61.90	116.4	54.19	0.35	2.44	1500
BSPK20			42															0.32		
BSPF25	42	65	—	52	74	50.3	9	26.5	M5	2	25	4	10.02	18.19	89.81	163.0	101.4	0.49	3.80	3000
BSPK25			50															0.46		
BSPF30	47	75	—	60	84	60	10	30	M6	2	30	4	11.48	22.09	122.3	235.4	153.7	0.69	5.49	3000
BSPK30			55															0.63		

呼び番号 **BSPF20 -1 -BSPK20 ×500**

スプラインナット型番 ————— スプライン軸長さ(L)

スプライン軸1本に使用するナット数 ————— スプライン軸型番