



表279 : MSKシリーズ寸法表

ナット型番	リード	ナット						主 要
		D	Df	PCD	K	L	T	
MSK 0401	1	10	23	15	15	11.5	3.5	
MSK 0402	2							
MSK 0601	1	12	26	18	17	14.5	3.5	
MSK 0602	2							
MSK 0609	9							
MSK 0618	18							
MSK 0801	1	14	29	21	18	18	4	
MSK 0802	2							
MSK 0812	12							
MSK 0824	24							
MSK 1002	2	16	33	24	21	22	5	
MSK 1006	6							
MSK 1010	10							
MSK 1015	15							
MSK 1030	30							
MSK 1202	2	18	35	26	22	25	5	
MSK 1204	4							
MSK 1208	8							
MSK 1212	12							
MSK 1218	18							
MSK 1236	36							
MSK 1505	5							
MSK 1510	10	24	42	33	27	30	6	
MSK 1520	20							
MSK 2010	10							
MSK 2020	20	30	50	40	32	36	7	

単位 : mm

寸 法	許容スラスト荷重	許容回転数	最大締付けトルク	質 量	ステンレス	ネジ軸主要寸法			質 量				
						ネジ軸型番	d	谷径 d <sub>1</sub>		標準軸長 ℓ	(kg/m)		
2.9	1	50	2000	2.09	MS 0401	4	3.3	200	0.08				
	2	60		2.09					MS 0402	0.08			
3.4	1	120	2000	2.89	MS 0601	6	5.3	300	0.19				
		60		2.86					MS 0602	0.20			
	4	90		2.80	MS 0609		0.21						
		70		2.77	MS 0618		0.21						
3.4	1	200	2000	4.00	MS 0801	8	7.3	300	0.35				
		290		4.08					MS 0802	0.32			
	4	210		3.97	MS 0812		0.34						
		210		3.94	MS 0824		0.36						
	4.5	1		460	1500		5.90		MS 1002	10	8.6	300	0.52
				370			5.78						MS 1006
4		250	5.76	MS 1010		0.54							
		410	5.83	MS 1015		0.52							
4.5	1	660	1000	7.24	MS 1202	12	10.6	300	0.77				
		620		7.48					MS 1204	0.72			
		820		7.46	MS 1208		0.73						
		470		7.08	MS 1212		0.82						
	6	750		7.17	MS 1218		0.77						
		540		7.10	MS 1236		0.80						
		1		890	800		16.39	MS 1505	15	12.2	2000	1.15	
				1040			15.73					MS 1510	1.13
1100	16.44		MS 1520	1.14									
2	1240	600	25.76	MS 2010	20	17.5	2000	2.16					
	1420		26.35					MS 2020		2.18			

呼び番号 ナット型番 ネジ軸型番  
 MSK 08 02 + MS 0802 - 300  
 ネジ軸外径 + MSC0802 - 150  
 リード + MSP0802 - 200  
 ネジ軸の種類 ネジ軸長さ