



表280 : MSKWシリーズ寸法表

ナット型番	ナット							リード
	D	Df	PCD	K	L	T		
MSKW 0401	10	23	15	15	17.5	3.5	1	
MSKW 0402							2	
MSKW 0601	12	26	18	17	23.5	3.5	1	
MSKW 0602							2	
MSKW 0609							9	
MSKW 0618							18	
MSKW 0801	14	29	21	18	29	4	1	
MSKW 0802							2	
MSKW 0812							12	
MSKW 0824							24	
MSKW 1002	16	33	24	21	35	5	2	
MSKW 1006							6	
MSKW 1010							10	
MSKW 1015							15	
MSKW 1030	18	35	26	22	40	5	30	
MSKW 1202							2	
MSKW 1204							4	
MSKW 1208							8	
MSKW 1212	24	42	33	27	48	6	12	
MSKW 1218							18	
MSKW 1236							36	
MSKW 1505							5	
MSKW 1510	30	50	40	32	57	7	10	
MSKW 1520							20	
MSKW 2010							10	
MSKW 2020							20	

単位 : mm

寸法	S	条数	許容スラスト荷重 Fa (N)	許容回転数 Nc (rpm)	最大締付けトルク (N・mm)	質量 (g)	ステンレス ネジ軸型番	ネジ軸主要寸法			質量 (kg/m)	
								d	谷径 d <sub>t</sub>	標準軸長 ℓ		
2.9	1	1	50	2000	250	2.62	MS 0401	4	3.3	200	0.08	
		2	60			2.62	MS 0402				0.08	
3.4	1	1	120	2000	600	3.95	MS 0601	6	5.3	300	0.19	
		2	60			3.92	MS 0602				0.20	
	4	1	90			3.81	MS 0609		5.4		0.21	
		2	70			3.77	MS 0618		5.6		0.21	
3.4	1	1	200	2000	600	5.58	MS 0801	8	7.3	300	0.35	
		2	290			5.67	MS 0802				6.6	0.32
	4	1	210			5.53	MS 0812		6.7		0.34	
		2	210			5.40	MS 0824		7.5		0.36	
4.5	1	1	460	1500	800	8.20	MS 1002	10	8.6	300	0.52	
		2	370			8.02	MS 1006				8.0	1000
	4	1	250			8.04	MS 1010		8.4		0.52	
		2	410			8.04	MS 1015		8.9		450	0.50
4.5	1	1	660	1000	800	10.30	MS 1202	12	10.6	300	0.77	
		2	620			10.66	MS 1204				10.0	1000
	2	1	820			10.64	MS 1208		9.8		0.73	
		2	470			9.96	MS 1212		10.3		0.82	
4.5	6	1	750	1000	800	10.15	MS 1218	12	10.6	500	0.77	
		2	540			10.03	MS 1236				10.9	0.80
	1	1	890			23.93	MS 1505		12.2		2000	1.15
		2	1040			22.94	MS 1510		12.3		1.13	
4.5	4	1	1100	800	800	24.00	MS 1520	15	12.6	2000	1.14	
		2	1240			37.62	MS 2010				17.5	2.16
	2	1	1420			38.41	MS 2020		17.6		2.18	
		2	1420			38.41	MS 2020		20		2000	2.18

呼び番号 MSKW 08 02 + MS 0802 - 300  
 ネジ軸外径 + MSC0802 - 150  
 リード + MSP0802 - 200  
 ネジ軸の種類                      ネジ軸長さ